

# A Method and Device of Controlling External System Parameters Using ATA Side Band

## TECHNICAL FIELD

The invention provides a device that offers a solution/method for controlling  
5 external system parameters. It is compatible with ATA/ATAPI by using of ATA  
protocol or side-band protocol to make a main system communicate with other  
devices through original ATA/ATAPI device's data cable. The process and result of  
message transfer would not cause any affection on ATA/ATAPI device; besides, it can  
achieve the goal of controlling external system parameters.

## 10 BACKGROUND OF THE INVENTION

Sub AI > The invention is a solution/method of transferring message through a data cable,  
specifically, the standard and non-standard controlling sequences can be co-existed in  
a system to transfer the defined original message under the standard controlling  
sequence and to transfer extra message under non-standard controlling sequence by  
15 the system connected the data cable to communicate with the correspond devices.  
Thus, external system parameters can be monitored and controlled, and the data cable  
would not affect the prior communication.

Generally, a data storage device system is connected to a data cable (ATA)  
plunged into a the connector, of other end of the cable is connected to an external

connection box device that has a hard driver or CD-ROM driver, for accessing or outputting message . Therein, the system must be equipped with a controlling sequence defined by ATA for transferring message. For gathering out of the external connector box's parameter messages (e.g. power switch on/off, indicator lamp on/off, 5 outer case's temperature and fan's rotating speed), the system must be added another data cables to connect with the external connection box device; the same as the external connection box device provides messages to others.

Above all, the system not only has to add specific-design loops but also has to add extra data cables for transferring and receiving message. Consequently, two pair 10 data cables and an added specific-design loop are necessary; however, it will increase production cost. Furthermore, the added data cables and loops will block heat air currents, which will result to over-heated problem. This is the most urgent issue shall/must be solved and improved for the usage of users by the invention.

The inventor has been working on related computer product research for many 15 years. Due to inconvenient for using of several data cables are necessary to transfer and receive message in a computer, the invention is developed for common using a single data cable (ATA) to connect the external connector box with the computer to read/access message or monitor parameters through it.

## SUMMARY OF THE INVENTION

The invention's primary objective is the solution/device of controlling external parameters by using of the same data cable and specific software to transfer / receive message and monitor/controlling external parameters in a system.

- 5        The secondary object is the solution/device of controlling external parameters by using of the system's data cables and non-standard controlling sequence to transfer and receive message by the same cable connected with external device for monitoring/ controlling external parameters. Hence the advantages are the data cables reduced, the loops simplified, the manufacture costs decreased, and a better heating
- 10    dissipation.

## BRIEF DESCRIPTION OF DRAWING

To make clearly understanding of the manufacturing process, structures, specifications, functions, and advantages of the invention, two practicable applications and diagrams shown as following:

- 15    Fig. 1 is the block diagram of the first practicable application.

Fig. 2 is the external accessing diagram of the first practicable application.

Fig. 3 is external system parameters monitoring diagram of the first practicable application.

Fig. 4 is the block diagram of the second practicable application.

## BRIEF DESCRIPTION OF THE TERMS

- system.....(20)      software program.....(21)
- standard controlling procedure.....(22)
- temporary store device of standard controlling procedure .....(221)
- 5 non standard controlling procedure.....(23)
- temporary store device of non-standard controlling procedure .....(231)
- data cable..... (30)      external machine.....(40)
- external System..... (41)      separator.....(42)
- external connection box device... (50)

## 10 DETAILED DESCRIPTION OF THE INVENTION

Please refer to Fig. 1 and 2 for of the first practicable application. It illustrates the device/solution of controlling external system parameter including a system (20), a data cable (30), an external machine (40) and an external connection box device (50).

- 15 Please refer to the Fig. 1. Illustrates the system (20) including a build-in software program (21) for receiving and transferring messages, and a standard controlling procedure (22)--under the ATA Association's specification--connected with the software program (21), and a non-standard controlling procedure (23)--not in the ATA Association's specification but specified by the manufactures or users.

The data cable (30) is manufactured and followed the specification--regulated by ATA Association--of ATA standard in the system (20). Of the one end of the cable (30) connected with a standard controlling procedure (22) and a non-standards controlling procedure (23); the other end connected with an external machine (40) and an external connection box device (50), of the external machine (40) connected with an external system (41) and a separator (42). The separator is allocated on the cable (30) and between the external machine (40) and the external connection box (50). In receiving and transferring signals of the external machine (40) and the external connection box (50) is channeled through the cable (30), and those signals are readable and defined by them to provide the accessible message to the software program (21) for using in the system (20).

The external machine (40) of this invention is capable as an interface in several approaches as following:

1. The external machine (40) comprises hardware and software for receiving the specified message transferred from the cable (30).
2. The external machine (40) comprises ASIC and FPGA for receiving side-band protocol transferred from the cable (30).
3. The external machine (40) comprises hardware, software, ASIC and FPGA for receiving a specified message or side-band protocol transferred from the cable (30).

The basic principle of the invention of controlling external system parameters is explained as following:

Under the ATA or ATAPI device-compatible environment, the system will receive and transfer the procedure of non- agreement of ATA or side-band protocol by using  
5 of a specified software program (21) to be operating and adopted the external machine (40) to receive and transfer those extra messages. Those extra messages are readable or in preset status in the external system (41), which are allowed to monitor in an appropriate way.

The methods of this invention of controlling external system parameters are  
10 described as followed:

1. Under a certain procedure, the system (20) receives the signals and processing/  
gathering them internally, then transferred to the software program (21) for  
operating. Please, refer to Fig. 1. The software program (21) will transfer the  
normal information-- defined by ATA Association--onto the standard controlling  
15 procedure (22), and save them in a relevant temporary store device (221) for  
acting. Accordingly, the normal message will be transferred/received onto the  
cable (30) under this approach.
2. As the system (20) receives the specified message to be operating by the software  
program (21). Please, refer to Fig. 1. The software program (21) will transfer

the specific information--not defined by ATA Association--onto the external machine (40) and save them in a relevant temporary store device (231) for acting. Accordingly, the specified message will be transferred/received onto the cable (30) under this approach.

5           Above all, the normal and specified message will be transferred through the cable (30). For the external machine (40) and external connection box device (50) will receive the two kinds of messages transferred from the cable (30), and the external machine (40) is in the stage of monitoring to monitor the message transferred from the cables (30).

10    3. Please, refer to Fig. 1. When the external machine (40) receives the specific message--not followed to ATA's Agreement but specified by manufactures or users-- from the cable (30). The external machine (40) will generate a signal to cut off the separator (42) to break the external connection box device (50) out and disconnect to the cable (30) for stopping further actions.

15    4. The non-ATA Association's definition model of specific agreement should corresponding match up with the external machine (40), so the external machine (40) can identify the specific messages transferred from the cable (30). When the external machine (40) receiving the specific signals that is followed the non-ATA Association, the external machine (40) will enter into an accessing/saving stage

externally.

5. The external machine (40) is in accessing/saving stage externally for the specific messages, which are provided by the external machine (40) as a switch that will not in concern of the external connection box. The external machine (40) provides specific signals to correspond the system's (20) specific temporary store device for a preset of reading and writing to control the external system to act, or to disclosure the stage of external system.

It is knowingly of above description. The invention adopts a data cable (30)--under the standard definition of ATA and a compatible environment-- to connect with the external connection box device (50)--the equipment of ATA/ATAPI--to be operating by the system's specific program through a presetting or reading/writing procedure in a specific temporary store device--out of ATA Association's definition. This specific procedure will be identified by the specific designed hardware, which is correspondent matching with external machine (40).

15 In general, the standard controlling procedures been defined by the ATA Association, which for transferring data of ATA/ATAPI's devices are under ATA Association's defined models (e.g. related documents and specifications). For this strict standard to be modeling the various manufactures makers to design and produce the devices of ATA/ATAPI and to make those devices (e.g. hard drivers, CD-ROM)



transfer data correctly. For the standard said the definition of the signals of bus, of every temporary store that providing/controlling to ATA's/ ATAPI's devices, of the procedures of command and combination, and of the relation of bus controlling signal sequences. For the controlling procedure sequence of ATA's/ATAPI's devices can  
5 be in three stages: 1) the presetting of controlling temporary device (standard address of 1F1h-1F6h), 2) the presetting of commanding temporary store device (standard address of 1F7h), and 3) message transferring. Please, refer to Fig. 2. Prior the stage 2, excluding the bits' presetting of software reset, otherwise there is no affection or error action to ATA's/ATAPI's devices.

10 For above account, the invention uses by the software program to execute a set of specific procedures of reading/resetting in controlling temporary device in stage 1; whereas not been by the specific software to operate or execute, so the specific procedure will not be occurred. Additionally, the specific procedure can be identified by the external system and its connector--external machine--to enter a  
15 saving/accessing stage. For the account of very strictly modeling pattern, sot any of unfit procedure will not allow to enter this stage, but in a status that has not in the stage' concern.

When an external machine identifies this specific procedure, which will enter to so-called external saving/accessing stage. Please, refer to Fig. 1. For resetting to

read /write in the stage, it has to be switching to external machine for providing the data, also is not in ATA's/ATAPI's concern. For example: writing a certain data in a certain controlling temporary device of the external machine, which will be saved and being seem as the provided signal to switch on/off of power or lamp. Other example

5 as: the external machine is in reading/accessing stage, for the data from a certain temporary device; of those data provided by the external device that means the data are the messages of external system's temperature and fan's rotating speed.

Wherein the external machine in reading/accessing stage, the software can be using of a so called deviated procedure, which makes the external machine deviate from  
10 reading/accessing stage and return to the original stage. This process can reach the purpose of controlling and monitoring the external parameters by the standard ATA's bus.

The second practical application of the invention is very similar to the first one. Please, refer Fig.4. The differences is the software program (21') of the system (20')  
15 controls the relevant temporary store device of the standard controlling procedure (22'). The standard controlling procedure being generating the standard signal sequence--defined by ATA--of the relevant temporary device of the procedure specified by ATA'S pattern. Under PIO model, its sequence signals/side-band protocol (CSO#) address will be triggered by the saving /accessing of the controlling

temporary store device. For the sequence signals (CSO#) address transferring the cable to be the receiving acting for the external connection box device (50). The non-standard controlling procedure (23') of the being generating the non-standard signal sequence--its controlling sequence defined under a specific pattern. For the

5 non-standard ATA's signal sequence of the relevant temporary device of non-standard controlling procedure, its sequence signals or (CSO#) address will be not triggered by the saving accessing of the controlling temporary store device. For the side-band protocol or (CSO#) address will not be acted and transferred though the data cable (30'), so the external connection box device (50') has no receiving action. For the

10 interface of the external machine (40') is the machine connected with ASIC and FPGA. As the signal sequence generated from non-standard controlling sequence (23') of the system (20'), the external machine (40') will receive the signal sequence transferred from the data cable (30').

The non-standard controlling procedure (23') and is correspondent external

15 machine (40') of the invention can identify the side-band protocol (CSO#) address generated from non-standard controlling procedure (23') but is no function sequence signal. Thereby, the system (20') can connect with a specific hardware, and the external connection box device (50')(ATA/ATAFI) the specific sequence, then, it will be transferred to an external machine (40'), available for identifying the specific

sequence. So, the external machine can isolate the external connection box device by the specific data and only provide by the external machine to the purpose of controlling and monitoring the external parameters.

In conclusion, the invention-- A Method and Device of Controlling External  
5 System Parameters Using ATA Side Band is using of connect the software program in the same cable for accessing the specific signal or side-band protocol to transfer or receive the specific message or signal ones. For the invention can simplify the cables and routes, and make no affection to the data cables and devices by using of the specific software to correspond external machine to read and reset the specific  
10 message to reach the external system parameters can be monitored. The invention has high utility in industry and high novelty and innovation therefore this invention will to meet the requirement of patent application.